



KEYTEC, INC.

A global leader of touch-interactive technology since 1987.



520 Shepherd Drive, Garland, Texas 75042 Tel: 1-800-MAGIC89 (USA toll free) 1-972-272-7555 Fax: 1-972-272-7501 Email sales@magictouch.com



KTSC-19V (Black) 19" Flat CRT Touch Monitor Specifications:

Monitor Specifications		Touch Screen specifications	
Size	19"	Technology	Resistive
View Area	18"	Material	Plastic on Glass
Display Type	Perfect Flat CRT	Surface Treatment	Anti-glare hard coating
Max. Resolution (PC)	1600 x 1200	Spacer	Invisible (patented)
Pixel	0.21-0.25 mm	Light Transmission	80% nominal
Horizontal Scan	30-97KHz	Scratch Resistance	3H pencil hardness min.
Vertical Scan	50-180Hz	Touch Resolution	USB: 4096 x 4096 Serial: 4096 x 4096
Video Signal	Analog	Interface Controller	External box, USB or Com port.
Colors	16 million	Controller Size (mm)	76.2 x 38.1 x19
Display Area (mm)	360 x 270	Power	5 VDC direct from computer.
Power (VAC)	90-264V, 50-60Hz	Operating Systems	Windows 95, 98, NT, ME, 2000, XP, Vista, Mac, Linux.
Power Consumption	98W maximum	Drivers	Mouse emulation (click/drag)
Operating Temperature	0 to 40 degrees C	Activation Force	50-120 grams per square cm
Storage Temperature	-20 to 60 degrees C	Response Time	< 0.1 sec.
Speakers	No	Position Accuracy	3 mm maximum error
USB hub	No	Touch Mode	Mouse click/drag functions
Dimensions (mm) WxHxD	445 x 424.8 x 465	Operating Temperature	-10 to 70 degrees C
Weight (KGs)	18	Storage Temperature	-30 to 85 degrees C
		Humidity	95%RH @ 40C for 96 hours
		Chemical Resistance	Resist to all cleaning chemicals
		Durability	3 million touches each point
Warranty	3-year parts & labor	Warranty	1-year parts/labor +2-year labor only for touch screen. 3-year parts/labor for controller.

Lifetime free drivers upgrade and technical support.

KEYTEC'S product is the "Best Buy" in touch screen industry.

www.magictouch.com