



**KEYTEC, INC.**

*A global leader of touch-interactive technology since 1987.*



520 Shepherd Drive, Garland, Texas, USA 75042 Tel: 972-272-7555 Email: [info@magictouch.com](mailto:info@magictouch.com)

OPTIR Touch General Specifications:

Item	Description
Input Method	Finger, Gloved Hand, Stylus.
Activation Force	Zero force
Accuracy	2 mm
Resolution	4096 x 4096
Response Time	100 RPS
Temperature	Operating : -20 ~ 70 degree C Storage : -40 ~ 85 degree C
Relative Humidity	Operating : 90% Storage : 95%
Operating Voltage	5.5V ~ 6V (DC adapter)
Operating Systems	XP/Vista/Win 7 & Linux & MAC
Controller	Built-In
Interface	USB
Frame	Black Aluminum
Certifications	CE / FCC / BSMI

Functions:

Mouse and tablet emulation.

Screen touched = left mouse button clicked

Touch down and drag = left mouse button held down and dragged

Tap twice = left mouse button double clicked

Swap Button: Select 'once' to right-click for one touch, or 'always' to always right-click. Select minimize to reduce to system tray. Click in tray as a shortcut!

Right Click in Vista and Win 7 tablet mode: Touch and hold.